



METAL REPAIR

PIPE REPAIR

WATERPROOFING

CONCRETE REPAIR

IMPACT & ABRASION

CHEMICAL PROTECTION

THERMAL PROTECTION

TECHNICAL FABRICS

UNDERWATER REPAIR

CORROSION PROTECTION

FLOOR PROTECTION

ACCESSORIES

2017 PRODUCT LIST

Code	Product Name	Product Description	Pack Size	Colour	Solids	Applications	Surface Prep	Coverage rate
METAL REPAIR SYSTEMS								
101	Metal Repair Paste	Two pack, solvent free epoxy repair paste	1kg 3kg	Dark Grey	100%	Rebuild pump/ valve casings, leaking pipes, flanges, scored hydraulic rams, engine blocks, worn/ damaged drive shafts	Mechanical Abrasive Blast	0.406m ² at 1mm 0.135m ² at 3mm Based on 1kg
102	Metal Repair Fluid	Two pack, solvent free epoxy repair fluid	1kg 3kg	Dark Grey	100%	Resurface damaged or worn metallic surfaces. Also used as an anti slip system when used with aggregates	Mechanical Abrasive Blast	0.44m ² at 1mm 0.147m ² at 3mm Based on 1kg
103	Metal Repair Stick	Fast curing solvent free epoxy putty	125gm	Dark Grey	100%	Emergency repairs to leaking tanks, pipes, flanges, pump/ valve casings	Manual Mechanical	N/A
104	Metal Repair Fluid XF	Fast curing two pack solvent free epoxy fluid	200gm 800gm	Light Grey	100%	Emergency repairs to leaking tanks, pipes, flanges, pump/ valve casings	Mechanical Abrasive Blast	0.485m ² at 1mm per 800gm
105	Aqua Stick	Fast curing solvent free underwater epoxy putty	125gm	Cream	100%	Emergency repairs to metallic surfaces underwater	Manual Mechanical	N/A
106	Metal Repair Paste XF	Fast curing solvent free epoxy repair paste	200gm 500gm	Light Grey	100%	Emergency repairs to leaking tanks, pipes, flanges, pump/ valve casings	Mechanical Abrasive Blast	0.278m ² at 1mm per 500gm
107	Metal Repair Paste XL	Extended working life solvent free epoxy paste	4kg	Dark Grey	100%	Rebuild pump/ valve casings, leaking pipes, flanges, scored hydraulic rams, engine blocks, worn/ damaged drive shafts	Mechanical Abrasive Blast	0.406m ² at 1mm per 1kg
302	Epoxy Repair Cement	Two pack solvent free epoxy fairing compound	1kg	Dark brown	100%	Fairing compound for metallic and composite surfaces	Manual Mechanical	0.625m ² at 1mm per 1kg
904	Release Agent	Single component solvent based wax	120ml	Clear	50%	Wax based release agent free of silicon and chlorohydrocarbons	Manual Mechanical	1.66m ² at 75 microns per 125ml

FLUID FLOW, ABRASION, IMPACT REPAIR SYSTEMS

UP TO 60°C IMMERSION

201	Ceramic Repair Paste	Two pack solvent free epoxy repair paste	1kg 3kg	Dark grey	100%	Rebuild pump/ valve casings, tube end plates, propellers, impellers, condenser tube sheets, separators, pipes, valves, rudders	Abrasive Blast	0.406m ² at 1mm Per 1kg 0.135m ² at 3mm Per 1kg
202	Ceramic Repair Fluid	Two pack solvent free epoxy fluid	1kg 3kg	Light Grey, Dark Grey, Blue	100%	Resurface pump/ valve casings, tube end plates, propellers, impellers, condenser tube sheets, separators, pipes, valves, rudders	Abrasive Blast	1.4m ² at 250 microns per 1kg
203	Super Flow Ceramic Fluid	Two pack solvent free epoxy fluid	1kg 3kg	Light Grey Dark Grey	100%	Flow efficiency coating for pump/ valve casings, tube end plates, propellers, impellers, separators, pipes, valves, rudders	Abrasive Blast	2.716m ² at 250 microns per 1kg
204	Heavy Duty Ceramic Repair Paste	Two pack solvent free epoxy paste with ceramic beads	5kg 25kg	Mid Grey Red, blue	100%	Rebuilding of substrates subject to heavy abrasion or impact such as dredging pumps, chutes, hoppers, pipe work	Abrasive Blast	0.117m ² at 5mm per 1kg
209	EIP-PU Extreme Impact Protection	Two pack solvent free high build, toughened polyurethane coating	1ltr	Light Grey Light Blue	100%	High build 100% solids toughened polyurethane coating designed to be applied to metallic or cementitious surfaces subject to high impact and wear. Coating is flexible and suitable for food contact	Abrasive Blast	1m ² at 1mm microns per 1ltr

HYDROCARBON, ALKALIS & SOLVENTS IMMERSION UP TO 130°C

205	Ceramic HT Fluid	Two pack solvent free epoxy novolac coating	1kg 3kg	Dark grey	100%	Resurfacing of metallic surfaces subject to high temperature erosion, <u>up to 130°C continuous immersion in solvents and hydrocarbons</u>	Abrasive Blast	0.85m ² at 500 microns per 1kg
-----	-------------------------	---	------------	-----------	------	--	----------------	--

ACIDS UP TO 110°C

206	Ceramic HTA Fluid	Two pack solvent free epoxy novolac coating	1kg 3kg	Dark grey	100%	Resurfacing of metallic surfaces subject to acid erosion at elevated temperatures, <u>up to 110°C continuous immersion in acids</u>	Abrasive Blast	0.85m ² at 500 microns per 1kg
-----	--------------------------	---	------------	-----------	------	---	----------------	--

UNDERWATER REPAIR AND COATING SYSTEMS

106	Metal Repair Paste XF	Fast curing solvent free epoxy repair paste	200gm 500gm	Light Grey	100%	Fast curing epoxy resin for sealing metallic surfaces underwater	Manual Hydroblast	0.278m ² at 1mm per 500gm
208	Ceramic UW	Two pack solvent free high build under water epoxy coating	4ltr	Dark grey	100%	Applied to hand prepared and hydroblasted surfaces at the waterline and underwater. Apply in a single coat at 1mm WFT.	Manual Hydroblast	1m ² at 1mm per 1ltr

PIPE & COMPOSITE REPAIR SYSTEMS

SURFACE FILLERS

101	Metal Repair Paste	Two pack, solvent free epoxy repair paste	1kg 3kg	Dark Grey	100%	Apply to badly corroded surfaces, can be used as the adhesive for plate bonding onto pipe surfaces	Mechanical Abrasive Blast	0.406m ² at 1mm 0.135m ² at 3mm Based on 1kg
103	Metal Repair Stick	Fast curing solvent free epoxy putty	125gm	Dark Grey	100%	Fast curing epoxy putty for plugging small holes in pipes	Manual Mechanical	N/A
106	Metal Repair Paste XF	Fast curing solvent free epoxy repair paste	200gm 500gm	Light Grey	100%	Fast curing epoxy paste for filling badly pitted pipe surfaces, fully cured in 60 mins	Mechanical Abrasive Blast	0.278m ² at 1mm per 500gm
302	Epoxy Repair Cement	Two pack solvent free epoxy fairing compound	1kg	Dark brown	100%	Surface tolerant trowel applied filler, ideal for large surface areas	Manual Mechanical	0.625m ² at 1mm per 1kg

FAST CURE LOW PRESSURE PIPE REPAIRS – UPTO 150psi

108	Pipe Repair Bandage	Water activated pipe repair bandage	50mm x 1.8mtr	White	100%	Seal leaking pipes up to 4" (100mm) in diameter, fully cured in 60 minutes	Manual	N/A
108	Pipe Repair Bandage	Water activated pipe repair bandage	50mm x 3.6mtr	White	100%	Seal leaking pipes up to 8" (200mm) in diameter, fully cured in 60 minutes	Manual	N/A
108	Pipe Repair Bandage	Water activated pipe repair bandage	75mm x 3.6mtr	White	100%	Seal leaking pipes up to 12" (300mm) in diameter, fully cured in 60 minutes	Manual	N/A
108	Pipe Repair Bandage	Water activated pipe repair bandage	100mm x 3.6mtr	White	100%	Seal leaking pipes up to 16" (400mm) in diameter, fully cured in 60 minutes	Manual	N/A

HIGH PRESSURE PIPE REPAIRS – UPTO 300psi

301	Epoxy Resin Hardener	Two pack solvent free epoxy repair gel	300gm 6kg	Opaque	100%	Seals leaking pipes, pipe bends, flanges, tank seams and tank bases when used with glass tape	Manual Mechanical	0.25m ² at 1mm per 300gm
701	Glass Tape	Woven glass fabric	50mm x 50mtr	White	N/A	To be used in conjunction with 301 Epoxy Resin and Hardener	N/A	1.25m ² with 50% overlap
703	Glass Tape	Woven glass fabric	100mm 50mtr	White	N/A	To be used in conjunction with 301 Epoxy Resin and Hardener	N/A	2.5m ² with 50% overlap

PIPE SEALING COMPOUND

580	Cast and Seal	Two pack solvent free pourable silicon coating	4ltr	Grey	100%	Pourable silicon coating designed to be poured into pipe collars to seal low pressure gas lines. Up to 250°C dry temperature resistance	Manual	0.20m ² at 20mm per 4ltr unit
-----	----------------------	--	------	------	------	---	--------	--

589	Silicon Adhesion Promoter	Single pack adhesion promoter	1ltr	Clear	N/A	Thin film adhesion promoter to be applied to hand prepared metallic surfaces	Manual	10m ² per unit
-----	----------------------------------	-------------------------------	------	-------	-----	--	--------	---------------------------

GRP HULL & STRUCTURES REPAIR

303	Life Boat Repair Kit	Two pack solvent free epoxy repair gel	300gm 6kg	Opaque	100%	Use with glass fibre matting to repair GRP structures and hulls	Manual	0.25m ² at 1mm per 300gm
705	Glass Cloth	Woven glass fabric	10 x 1m ²	N/A	N/A	To be used in conjunction with 301 Epoxy Resin and Hardener	N/A	10m ² per pack
706	Glass Mat	Glass strand matting	10 x 0.5m ²	N/A	N/A	To be used in conjunction with 301 Epoxy Resin and Hardener	N/A	5m ² per pack

PIPE, COMPOSITE & ENGINEERING REPAIR KITS

GRP PIPE REPAIR KITS

601	Marine A Kit	Epoxy and glass fibre repair kit	N/A	N/A	100%	Repair kit containing composite materials, capable of 20 repairs to pipes THISTLEBOND EQUIVALENT	N/A	Please speak to Resimac for further info
602	Marine C Kit	Epoxy and glass fibre repair kit	N/A	N/A	100%	Repair kit containing various epoxy resin systems capable of 5 repairs THISTLEBOND EQUIVALENT	N/A	Please speak to Resimac for further info

METAL & CERAMIC MARINE REPAIR KITS

604	Marine Kit 1	Epoxy Metal Repair, Ceramic Repair kit	N/A	N/A	100%	Wide range of epoxy metal repair, ceramic repair, high temperature coatings WENCON EQUIVALENT	N/A	Please speak to Resimac for further info
605	Marine Kit 2	Epoxy Metal Repair, Ceramic Repair kit	N/A	N/A	100%	Wide range of epoxy metal repair, ceramic repair, high temperature coatings WENCON EQUIVALENT	N/A	Please speak to Resimac for further info
606	Marine Kit 3	Epoxy Metal Repair, Ceramic Repair kit	N/A	N/A	100%	Wide range of epoxy metal repair, ceramic repair, high temperature coatings WENCON EQUIVALENT	N/A	Please speak to Resimac for further info
607	Marine Kit 4	Epoxy Metal Repair, Ceramic Repair kit	N/A	N/A	100%	Wide range of epoxy metal repair, ceramic repair, high temperature coatings WENCON EQUIVALENT	N/A	Please speak to Resimac for further info

CHEMICAL PROTECTION – STEEL

LOW CONCENTRATION CHEMICAL IMMERSION UP TO 60°C

501	Resichem CRSG	Two pack solvent free epoxy coating	3.4ltr 16ltr	Light Grey, Dark Grey, Blue	100%	High build chemical coating for steel structures, tank lining, internal/external pipe surfaces	Mechanical Abrasive Blast	4m ² at 250 microns per 1ltr
-----	----------------------	-------------------------------------	-----------------	-----------------------------------	------	--	---------------------------	---

HIGH CONCENTRATION CHEMICAL IMMERSION UP TO 60°C								
511	Resichem UCEN	Two pack solvent free epoxy coating	4ltr 16ltr	Dark Grey, Red	100%	Ultimate chemical resistant coating capable of resisting 98% sulphuric acid, ideal for tank linings, steel structures and pipe lines	Abrasive Blast	2m ² at 500 microns per 1ltr
HIGH CONCENTRATION CHEMICAL IMMERSION UP TO 60°C - 90°C								
512	Resichem UCEN 90	Two pack solvent free epoxy coating	4ltr 16ltr	Light Grey, Red	100%	Ultimate chemical resistant coating capable of resisting 98% sulphuric acid at 75°C	Abrasive Blast	1m ² at 1mm per 1ltr
CHEMICAL PROTECTION – CONCRETE								
PRIMERS								
503	Resichem SPEP	Two pack solvent free low viscosity epoxy primer	4ltr 18ltr	Opaque	100%	Low viscosity epoxy primer designed to seal porous surfaces such as concrete	Mechanical Abrasive Blast	6.66m ² at 150 microns per 1ltr
505	Resichem Damp Seal	Two pack solvent free epoxy for damp surfaces	4.5ltr	Opaque	100%	Medium viscosity epoxy primer to seal damp porous surfaces	Mechanical	6.66m ² at 150 microns per 1ltr
LOW CONCENTRATION CHEMICAL IMMERSION UP TO 60°C								
501	Resichem CRSG	Two pack solvent free epoxy coating	3.4ltr 16ltr	Light Grey, Dark Grey, Blue	100%	High build chemical coating for floors, bunds, containment areas, tank linings, capable of brush or spray application	Mechanical Abrasive Blast	4m ² at 250 microns per 1ltr
HIGH CONCENTRATION CHEMICAL IMMERSION UP TO 60°C								
511	Resichem UCEN	Two pack solvent free epoxy coating	4ltr 16ltr	Dark Grey, Red	100%	Ultimate chemical resistant coating capable of resisting 98% sulphuric acid, idea for tank linings, structures, bunds, containment areas	Abrasive Blast	2m ² at 500 microns per 1ltr
HIGH CONCENTRATION CHEMICAL IMMERSION UP TO 60°C - 90°C								
512	Resichem UCEN 90	Two pack solvent free epoxy coating	4ltr 16ltr	Light Grey, Red	100%	Ultimate chemical resistant coating capable of resisting 98% sulphuric acid at 75°C, or 75% sulphuric acid at 90°C. Ideal for tank linings, structures, containment, pipelines	Abrasive Blast	1m ² at 1mm per 1ltr
FLEXIBLE CHEMICAL PROTECTION - SHORT TERM IMMERSION (72HRS) IN HIGH CONCENTRATION CHEMICALS								
583	Chemisil UC	Single component silicon based coating	4ltr	White/ Grey	100%	High build silicon coating designed to be applied in a single coat onto primed surfaces. Ideal for short immersion in sodium hypochlorite, acetic and nitric acid	Mechanical Abrasive Blast	1m ² at 1mm per 1ltr
589	Silicon Adhesion Promoter	Single pack adhesion promoter	1ltr	Clear	N/A	Thin film adhesion promoter to be applied to prepared concrete surfaces	Mechanical Abrasive Blast	10m ² per unit

CORROSION PROTECTION - STEEL

BASE COAT

501	Resichem CRSG	Two pack solvent free epoxy coating	3.4ltr 16ltr	Light Grey, Dark Grey, Blue	100%	High build epoxy coating for steel structures, external tank surfaces capable of brush or spray application	Mechanical Abrasive Blast	4m ² at 250 microns per 1ltr
506	Resichem Aluprime	Two pack solvent based epoxy coating	4ltr 20ltr	Dark grey	85%	Solvent based thin film corrosion coating for manual or mechanically prepared surfaces	Manual Mechanical	10m ² at 100 microns per 1ltr
507	Resichem DWPU	Two pack solvent free polyurethane coating	1ltr 4ltr	Light Grey Light Blue	100%	WRAS approved high build PU coating for steel structures. Ideal for tanks, pumps, valves and fittings	Mechanical Abrasive Blast	2m ² at 500 microns per 1ltr

UV STABLE TOP COAT

508	Resichem UVPU	Two pack solvent based Polyurethane UV stable coating	5ltr	Wide range of RAL and BS colours	55%	UV stable cosmetic finish compatible with all epoxy and polyurethane coatings	Mechanical Abrasive Blast	6.66m ² at 150 microns per 1ltr
555	Resinox	Single component water based acrylic	20ltr	Wide range of RAL and BS colours	55%	UV stable anti corrosion coating designed to be applied to hydro-blasted and mechanically prepared surfaces	Mechanical Hydro Blasted	2m ² at 500 microns per 1ltr
554	RB Membrane	Single pack solvent based rubberised membrane	5ltr 20ltr	White, Light Grey	40%	Rubberised membrane for manually prepared metallic surface. Shower resistant after 15mins and has low temperature cure	Manual Mechanical	2m ² at 500 microns per 1ltr

CORROSION PROTECTION – STEEL – HOT SURFACES UPTO 240°C

530	HA100	Single component heat activated epoxy novolac	4ltr	Red	100%	Heat activated epoxy novolac coating, designed to be applied to surfaces ranging from 95°C-240°C. Ideal for hot process surfaces for CUI protection	Mechanical	4m ² at 250 microns per 1ltr
-----	-------	---	------	-----	------	---	------------	---

CORROSION PROTECTION - CONCRETE

PRIMERS

503	Resichem SPEP	Two pack solvent free low viscosity epoxy primer	4ltr 18ltr	Opaque	100%	Low viscosity epoxy primer designed to seal porous surfaces such as concrete	Mechanical Abrasive Blast	6.66m ² at 150 microns per 1ltr
505	Resichem Damp Seal	Two pack solvent free epoxy for damp surfaces	4.5ltr	Opaque	100%	Medium viscosity epoxy primer to seal damp porous surfaces	Mechanical	6.66m ² at 150 microns per 1ltr

NON-UV STABLE TOP COAT								
501	Resichem CRSG	Two pack solvent free epoxy coating	3.4ltr 16ltr	Light Grey, Dark Grey, Blue	100%	High build epoxy coating for structures, external surfaces, cementitious surfaces, capable of brush or spray application	Mechanical Abrasive Blast	4m ² at 250 microns per 1ltr
507	Resichem DWPU	Two pack solvent free polyurethane coating	1ltr 4ltr	Light Grey Light Blue	100%	WRAS approved high build PU coating for concrete structures, containment, bunds and floors	Mechanical	2m ² at 500 microns per 1ltr
UV STABLE TOP COAT								
508	Resichem UVPU	Two pack solvent based Polyurethane UV stable coating	5ltr	Wide range of RAL and BS colours	55%	UV stable cosmetic finish compatible with all epoxy and polyurethane coatings	Mechanical Abrasive Blast	6.66m ² at 150 microns per 1ltr
555	Resinox	Single component water based acrylic	20ltr	Wide range of RAL and BS colours	55%	UV stable anti corrosion coating designed to be applied to hydroblasted and mechanically prepared surfaces	Mechanical Hydro Blasted	2m ² at 500 microns per 1ltr
554	RB Membrane	Single pack solvent based rubberised membrane	5ltr 20ltr	White, Light Grey	40%	Rubberised membrane for manually prepared metallic surface. Shower resistant after 15mins and has low temperature cure	Manual Mechanical	2m ² at 500 microns per 1ltr
556	Clear Cladding	Single pack concentrate diluted with water	1ltr	Opaque	100%	Mix with 9ltr of water to create a porous waterproofing system for concrete/stone	Water Jet	1.5m ² per 1ltr of diluted product
FLEXIBLE WATERPROOFING MEMBRANES								
FLEXIBLE WATER BASED ACRYLIC MEMBRANES								
550	WR Membrane	Single pack water based acrylic high build coating	20ltr	White, Light Grey	60%	High build membrane for waterproofing concrete and steel surfaces such as tank bases	Mechanical	2m ² at 500 microns per 1ltr
552	CSM Membrane	Thixotropic single pack water based acrylic used with glass fibre matting	20ltr	White, Light Grey	55%	Thixotropic coating for use with 200gm glass fibre chop strand matting, ideal for tank bases or flat roofs where added protection is required	Mechanical	1m ² at 1mm per 1ltr
FLEXIBLE SOLVENT BASED ACRYLIC ROOFING MEMBRANE								
551	ER Membrane	Fibrous single pack solvent based acrylic coating	5kg 20kg	White, Light Grey	55%	High build emergency coating for leaking gutters, felt surfaces, concrete and steel.	Manual Mechanical	0.7m ² at 1mm per 1kg

HEAT & THERMAL PROTECTION - STEEL

FAST CURING THERMAL COATING

560	Thermal Barrier XF	Two pack solvent free high build epoxy insulative coating	1ltr 4ltr 13ltr	Grey	100%	Designed to reduce heat transfer from underlying hot surfaces. Can be applied at temps from 5°C to 50°C. Once cured will give thermal protection up to 140°C.	Manual Mechanical	0.5m ² at 2mm per 1ltr
-----	---------------------------	---	-----------------------	------	------	---	----------------------	-----------------------------------

THERMAL COATING

561	Thermal Barrier	Two pack solvent free high build epoxy insulative coating	1ltr 4ltr 13ltr	Grey	100%	Designed to reduce heat transfer from underlying hot process surfaces. Must be applied to surface temps from 50°C to 110°C. Once cured will give thermal/ heat protection up to 140°C.	Manual Mechanical	1m ² at 1mm per 1ltr (dependent on surface temp)
-----	------------------------	---	-----------------------	------	------	--	----------------------	---

CHEMICAL RESISTANT THERMAL COATING

562	Novotherm 200	Three part epoxy novolac based insulative coating	6.5ltr	Dark Grey, Red	100%	Designed to reduce heat transfer from underlying hot process surfaces. Must be applied to surface temps from 10°C to 40°C. Once cured will give highly chemical resistant thermal/ heat protection up to 200°C.	Mechanical Abrasive Blast	0.5m ² at 2mm per 1ltr
-----	----------------------	---	--------	-------------------	------	---	------------------------------	-----------------------------------

ULTRA HIGH TEMPERATURE THERMAL COATINGS

563	Siltherm 250	Single component silicon based insulative coating	5ltr	White/ grey	100%	Designed to reduce heat transfer from underlying hot process surfaces. Must be applied to surface temps from 10°C to 40°C. Once cured will give thermal/ heat protection up to 250°C.	Mechanical Abrasive Blast	1m ² at 1mm per 1ltr
589	Silicon Adhesion Promoter	Single pack adhesion promoter	1ltr	Clear	N/A	Adhesion promoter for use with 563 Siltherm 250 when applied to metallic surfaces	Mechanical Abrasive Blast	10m ² per unit
564	Acrytherm 180	Single component acrylic based insulative coating	5ltr	White	55%	Designed to reduce heat transfer from underlying hot process surfaces. Must be applied to surface temps from 10°C to 30°C. Once cured will give thermal/ heat protection up to 180°C.	Mechanical Abrasive Blast	4m ² at 250 microns per 1ltr

PLEASE SPEAK TO RESIMAC FOR GUIDANCE ON WHICH SYSTEM TO USE

FLOOR COATING - CONCRETE

590	Epoxy FC	2 component solvent free epoxy floor coating with a gloss finish	25kg	Red, grey, green, blue	100%	2 component high build gloss finish floor coating applied in 2 x coats. Suitable for warehouse and light industrial flooring	Mechanical Abrasive Blast	76m ² at 250 microns per 25kg
591	Epoxy SL	3 component self-levelling floor coating	15kg	Natural, Grey	100%	3 component solvent free epoxy system with base, activator and aggregate for concrete floors	Mechanical Abrasive Blast	3.75m ² at 2mm per 15kg
592	Epoxy DF	3 component solvent free epoxy decorative floor coating	2 x 4ltr resin 25kg quartz	Wide range of colours available	100%	Multi component flooring system, including self-priming base coat, coloured quartz aggregate 1-2mm, colour fast top coat. Ideal for anti-slip flooring applications	Mechanical Abrasive Blast	8m ² per pack
593	Epoxy AS	2 component solvent free epoxy anti-static floor coating	5kg	Dark grey, black	100%	Epoxy based coating system suitable for use in areas where a resistance of less than 108 ohms is required as a measure to control static electricity	Mechanical Abrasive Blast	15m ² at 250 microns per 5kg

CONCRETE REPAIR

PATCH REPAIR & RESURFACING

570	Concrete Patch Repair XF	Three part solvent free fast curing epoxy repair mortar	5kg	Natural	100%	Fast curing repair mortar for cementitious surfaces, applied to manual prep surfaces.	Mechanical	0.47m ² at 5mm per unit
576	Quartz Screed	3 component solvent free epoxy repair screed	10kg 45kg	Natural Light grey	100%	Solvent free epoxy repair screed rebuilding cracked/damaged porous surfaces	Mechanical	0.42m ² at 10mm per 10kg

CHEMICAL RESISTANT

577	Chem Screed	3 component solvent free epoxy chemical screed	30kg	Dark grey, red	100%	Designed to rebuild damage floors and structures subject to chemical attack	Mechanical	1.35m ² at 10mm per 30kg
-----	-------------	--	------	----------------	------	---	------------	-------------------------------------

LIGHTWEIGHT

571	Concrete Repair LW	Three part solvent free light weight epoxy repair mortar	2.5kg	Natural	100%	Epoxy repair mortar for overhead cementitious surfaces	Mechanical	0.47m ² at 5mm per unit
-----	--------------------	--	-------	---------	------	--	------------	------------------------------------

DAMP, WATER SEEPAGE & WATER INFILTRATION

572	Concrete Seal CWC	Single component cementitious screed	25kg	Grey	N/A	Cement based screed designed for porous surfaces suffering from ingress of moisture, capable of resisting 140psi positive/negative hydrostatic pressure	Mechanical	2.5m ² at 6mm per 25kg unit
573	Fastfill Screed	Single component fast curing cementitious screed	25kg	Grey	N/A	Fast curing version of 572 Concrete Seal CWC with 140psi positive/ negative hydrostatic pressure, fully cures in 24 hours	Mechanical	1.33m ² at 10mm per 25kg unit

574	Fastfill Plug	Single component fast curing mortar	8kg	Grey	N/A	Cement based mortar, extremely fast curing, designed to stop water seepage and infiltration under pressure on porous surfaces, cures in 2-3minutes	N/A	0.42m ² at 20mm per 8kg unit
EXPANSION JOINTS								
575	Expansion Joint Filler	Two pack solvent free poly sulphide filler	4.5ltr	Black Dark Grey	100%	Highly flexible expansion joint filler that can be poured into primed expansion joints	Mechanical	1.33 linear mtr per ltr 25mm x 25mm joint
Technical Fabrics								
801	Flextech 100	Woven technical fabric	1.5mtr x 100mtr	N/A	N/A	To be used in conjunction with 503 SPEP and 505 Damp Seal	N/A	N/A
802	Flextech 200	Woven technical fabric	1.5mtr x 100m	N/A	N/A	To be used in conjunction with 503 SPEP and 505 Damp Seal	N/A	N/A
803	Flextech 300	Woven technical fabric	1.5mtr x 100mtr	N/A	N/A	To be used in conjunction with 503 SPEP and 505 Damp Seal	N/A	N/A
804	300 gm Chopstrand mat	Glass strand matting	1mtr x 100mtr	N/A	N/A	To be used in conjunction with 301 Epoxy Resin and Hardener, 503 SPEP and 505 Damp Seal	N/A	N/A
805	200gm Glass fabric	Woven glass fabric	1mtr x 100mtr	N/A	N/A	To be used in conjunction with 301 Epoxy Resin and Hardener	N/A	N/A
806	26gm polyester mesh	Light weight polyester mesh	1mtr x 100mtr	N/A	N/A	To be used to strengthen acrylic membranes and polyurethane coatings	N/A	N/A
807	Reinforcement Tape	Heavy weight polyester mesh	75mm x 200mtr	N/A	N/A	Heavy weight polyester mesh to be used with metal and ceramic repair products	N/A	N/A
808	Reinforcement Tape	Heavy weight polyester mesh	75mm x 4mtr	N/A	N/A	Heavy weight polyester mesh to be used with metal and ceramic repair products	N/A	N/A
ACCESSORIES								
705	Glass Cloth	Woven glass fabric	10 x 1m ²	N/A	N/A	To be used in conjunction with 301 Epoxy Resin and Hardener	N/A	N/A
706	Glass Mat	Glass strand matting	10 x 0.5m ²	N/A	N/A	To be used in conjunction with 301 Epoxy Resin and Hardener	N/A	N/A

709	Resin Cream		1kg	N/A	N/A	Hand cream for removing epoxy resin	N/A	N/A
901	Mixing Board	Clear polypropylene sheet	400mm 300mm	N/A	N/A	N/A	N/A	N/A
902	Spatula	Green plastic	40mm 280mm	N/A	N/A	N/A	N/A	N/A
903	Applicator Tool	Green plastic	95mm 145mm	N/A	N/A	N/A	N/A	N/A
905	MEK Cleaner	Solvent cleaner	500ml	N/A	N/A	Recommended cleaner for metallic surfaces	N/A	N/A
906	Nickel Anti Seize	High temperature lubricating & assembly paste	500gm	N/A	N/A	Protects against the seizure of metallic parts with a working temperature range of 200°C to 1350°C	N/A	N/A